

Technical Data Sheet



For domestic range hoods according to (EU) No 65/2014 and (EU) No 66/2014

| | |
|--------------------------------------------------------------------|-----------------------------------------|
| Supplier's name or trade mark | Belling |
| Type /Description | 444443573 BELLING 90 DB FLAT MK3 BLK |
| Energy efficiency class 1 | D |
| Annual energy consumption | 68 KWh/a |
| Fluid Dynamic Efficiency class 2 | F |
| Lighting efficiency class | A |
| Grease Filtering Efficiency class | B |
| Maximum air flow | 481.3 m ³ /h |
| Measured air flow rate at best efficiency point | 292.9 m ³ /h |
| Measured air pressure at best efficiency point | 93 Pa |
| Measured electric power input at best efficiency point | 106.1 W |
| Average illumination of the lighting system on the cooking surface | 146 lux |
| Measured power consumption in standby mode | / |
| Measured power consumption off mode | 0 W |
| Sound power level | 61 dB |
| Mounting | Wall Mounted |
| Size | 900 mm |
| Rated Power | 113 W |
| Rated voltage/ frequency | 220-240 V 50/60Hz |

Note

1 A (highest efficiency) to F (lowest efficiency)

2 A (highest efficiency) to F (lowest efficiency)

The above values have been measured in accordance with standards under specified operating condition

The above is based on the European Union's standards and rules