

Data sheet for household cooker hoods

In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele			
Model name / identifier		DA 2660	
Annual Energy Consumption (AEC _{hood})	kWh/year		38,5
Energy efficiency class			
A+ (most efficient) to F (least efficient)			A
Energy efficiency index (EEI _{hood})			49,7
Fluid Dynamic Efficiency (FDE _{hood})			32,2
Fluid Dynamic Efficiency class			
A (most efficient) to G (least efficient)			A
Lighting Efficiency (LE _{hood})	lx/W		53,3
Lighting Efficiency class			
A (most efficient) to G (least efficient)			A
Grease Filtering Efficiency	%		95,8
Grease Filtering Efficiency class			
A (most efficient) to G (least efficient)			A
Airflow at best efficiency point	m ³ /h		330,6
Air flow (min. speed)	m ³ /h		220
Air flow (max. speed)	m ³ /h		380
Air flow (intensive or boost setting)	m ³ /h		600
Max. air flow (Q _{max})	m ³ /h		600
Air pressure at best efficiency point	Pa		365
Airborne acoustical A-weighted sound power emissions (min. speed)	dB		42
Airborne acoustical A-weighted sound power emissions (max. speed)	dB		53
Airborne acoustical A-weighted sound power emissions (intensive or boost setting)	dB		64
Electrical power input at best efficiency point	W		104,0
Power consumption in off mode (P _o)	W		
Power consumption in standby mode (P _s)	W		0,15
Nominal power of lighting system	W		9,0
Average illumination of the lighting system on the cooking surface	lx		480
Time increase factor			0,8