

Itemname	FGM91X
<b>Energy data</b>	
EEI - Energy Efficiency Index (Class - Value)	<b>E - 100,4</b>
AEC - Annual Energy Consumption (kWh/a)	<b>86</b>
FDE - Fluid Dynamic Efficiency (Class - Value)	<b>F - 6,4</b>
LE - Lighting Efficiency (Class - Value)	<b>F - 7,5</b>
GFE - Grease Filter Efficiency (Class - Value)	<b>G - 44,2</b>
RU - Noise level (dB)	<b>60</b>
Min air flow in normal use QMIN (m3/h)	372
Max air flow in normal use QMAX (m3/h)	398.6
Air flow at intensive/boost setting QBOOST (m3/h)	no
Measured air flow rate at best efficiency point QBEP (m3/h)	231.4
Measured air pressure at best efficiency point PBEP (PA)	87
A-weighted Sound Power Emission EN60704 at minimum speed DBMIN (dBa)	55
A-weighted Sound Power Emission EN60704 at maximum speed DBMAX (dBa)	60
A-weighted Sound Power Emission EN60704 at intensive or boost speed DBBOOST (ducted-recirculating) (dBa)	no
Measured electric power input at best efficiency point WBEP (W)	87.5
Power consumption off mode PO (W)	0
Power consumption stand by mode PS (W)	0
Nominal power of the lighting system WL (W)	40
Average illumination of the lighting system on the cooking surface EMIDDLE (lux)	300
Time increase factor f	1.8
<b>Max Air flow EN61591 (ducted / recirculating) m3/h</b>	
Air flow EN61591 1st speed (ducted / recirculating) m3/h	322.5/193.5
Air flow EN61591 2nd speed (ducted / recirculating) m3/h	378.6/216
Air flow EN61591 3rd speed (ducted / recirculating) m3/h	527.06/290
Air flow EN61591 4th speed (ducted / recirculating) m3/h	