Product Fiche compliant to commission delegated regulation (EU) No 65/2014			
Brand	HOTPOINT		
Model	DH93CX S		
EEI [%] Energy Efficiency Index - Main cavity 1)	106.9		
EEI [%] Energy Efficiency Index - Secondary cavity 1)	106.9		
Energy Efficiency Class - Main cavity 2)	A		
Energy Efficiency Class - Secondary cavity 2)	A		
Energy consumption in conventional mode [kWh/cycle] - Main cavity 3)	0		
Energy consumption in conventional mode [kWh/cycle] - Secondary cavity 3)	0.76		
Energy consumption in fan-forced mode [kWh/cycle] - Main cavity 3)	0.9		
Energy consumption in fan-forced mode [kWh/cycle] - Secondary cavity 3)	0		
Energy consumption in conventional mode [MJ/cycle] - Main cavity 3)	0		
Energy consumption in conventional mode [MJ/cycle] - Secondary cavity 3)	0		
Energy consumption in fan-forced mode [MJ/cycle] - Main cavity 3)	0		
Energy consumption in fan-forced mode [MJ/cycle] - Secondary cavity 3)	0		
Number of cavities	2		
Heat source - Main cavity	ELECTRICITY		
Heat Source - Secondary cavity	Electric		
Usable volume [I] - Main cavity	74		
Usable volume [I] - Secondary cavity	39		

1) Energy Efficiency Index calculated according to the volume and energy consumption for each cavity.

2) From A+++ (low consumption) to D (high consumption).

3) Based on the results of standards tests that simulate the thermal properties of food. The consumption will depend on how the appliance is used.

Product Information compliant to commission regulation (EU 66/2014			
	Symbol	Value	Unit
Model identification		HOTPOINT	
Type of oven		FAN- FORCED	
Mass of the appliance	М	58.4	Kg
Number of cavities		2	
Heat source per cavity (electricity or gas)		ELECTRICI TY	
Volume per cavity - Main cavity	V	74	I
Volume per cavity - Secondary cavity	V	39	I
Energy consumption (electricity) required to heat a standardised load in a cavity of an electric heated oven during a cycle in conventional mode per cavity (electric final energy) - Main cavity	ECelectric cavity	0.00	kWh/cy cle
Energy consumption (electricity) required to heat a standardised load in a cavity of an electric heated oven during a cycle in conventional mode per cavity (electric final energy) - Secondary cavity	ECelectric cavity	0.76	kWh/cy cle
Energy consumption required to heat a standardised load in a cavity of an electric heated oven during a cycle in fan-forced mode per cavity (electric final energy) - Main cavity	ECelectric cavity	0.90	kWh/cy cle
Energy consumption required to heat a standardised load in a cavity of an electric heated oven during a cycle in fan-forced mode per cavity (electric final energy) - Secondary cavity	ECelectric cavity	0.00	kWh/cy cle
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in conventional mode per cavity (gas final energy) - Main cavity 1)	ECgas cavity	0.00	MJ/cycl e
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in conventional mode per cavity (gas final energy) - Main cavity	ECgas cavity	0.00	kWh/cy cle
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in conventional mode per cavity (gas final energy) - Secondary cavity 1)	ECgas cavity	0.00	MJ/cycl e
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in conventional mode per cavity (gas final energy) - Secondary cavity	ECgas cavity	0.00	kWh/cy cle
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in fan-forced mode per cavity (gas final energy) - Main cavity 1)	ECgas cavity	0.00	MJ/cycl e
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in fan-forced mode per cavity (gas final energy) - Main cavity	ECgas cavity	0.00	kWh/cy cle
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in fan-forced mode per cavity (gas final energy) - Secondary cavity 1)	ECgas cavity	0.00	MJ/cycl e
Energy consumption required to heat a standardised load in a gas-fired cavity of an oven during a cycle in fan-forced mode per cavity (gas final energy) - Secondary cavity	ECgas cavity	0.00	kWh/cy cle

Energy Efficiency Index per cavity - Main cavity	EElcavity	106.9	
Energy Efficiency Index per cavity - Secondary cavity	EElcavity	106.9	

1) 1kWh/cycle = 3,6 MJ/cycle