

## Specification Details Product: Dryers F082532 [IDCE G45X B H PS(NL)]

Owner nicola.silvestrelli  
 Originated 31-Aug-2012  
 Modified 20-Jul-2016  
 State [Released](#)

View   [Coding parameters](#)

### Coding parameters

<b>Business</b>	Free Standing	<b>Family</b>	Condenser standard
<b>Series 1</b>	8,0 Kg	<b>Series 2</b>	Electronic
<b>Aesthetic</b>	Indesit Eco Time	<b>User Interface</b>	DR_Digit
<b>Brand</b>	Indesit	<b>Trade Mark</b>	Indesit
<b>Noise (dBA)</b>	68	<b>Mix Segment</b>	DR_Condenser Electr 8,0Kg B
<b>Color</b>	White	<b>EAN 13</b>	8007842825329
<b>Range</b>	M.D.A.		

### General Information

<b>Sèche-linge</b>	AUTOMATIC , Condensign	<b>Markets</b>	NL-Holland	<b>Colour Leading Code</b>
--------------------	---------------------------	----------------	------------	----------------------------

### Energy Label

<b>Regulation</b>	2012	<b>Regulation Note</b>	
<b>Energy Class</b>	B	<b>Energy Info</b>	B

#### EU 1998 or OTHER DEDICATED

<b>Energy Class OD</b>	B	<b>Energy Info OD</b>	B
<b>Profondità</b>		<b>Max. drying capacity for cotton cycle ready to iron kg</b>	8.0
<b>Max. drying capacity for cotton cycle kg</b>	8.0	<b>Max. drying capacity for Easy Care Kg</b>	3
<b>Energy consumption for cotton cycle kW/h</b>	4.49	<b>Average consumption per year kW/h</b>	289.0
<b>Energy consumption for cotton cycle ready to iron kW/h</b>	3.8	<b>Energy consumption for Easy Care kW/h</b>	1.41
<b>Noise (dBA)</b>	68	<b>Drying time for cotton cycle ready to iron min</b>	105
<b>Drying time for Easy Care min</b>	65		
<b>Drying time for cotton cycle min</b>	140		

#### 2012 PROGRAMS STANDARD

<b>Rated capacity in kg of cotton full load</b>	8.0	<b>The weighted Annual Energy Consumption (AEc)</b>	560.0
<b>Energy consumption in kWh full load (Edry)</b>	4.77	<b>Energy consumption in kWh partial load (Edry ½)</b>	2.53
<b>Programme time full load (Tdry)</b>	139	<b>Programme time partial load (Tdry½)</b>	78
<b>Programme time weighted full &amp; partial load (Tt)</b>	104	<b>Duration of the 'left-on mode' for power management</b>	30
<b>Power consumption in Watts left-on mode (PI)</b>	2.39	<b>Power consumption in Watts Off-mode (Po)</b>	0.14
<b>Condensation efficiency class</b>	B	<b>Av. condensation eff in %, full load (Cdry)</b>	82
<b>Av. condensation eff in %, partial load. (Cdry½)</b>	80	<b>Av. condensation eff in %, weighted full &amp; partial load (Ct)</b>	81
<b>Acoustical noise expressed in dB(A) for full load.</b>	68	<b>Energy Efficiency Index</b>	75.8

#### 2014 ECODESIGN

<b>Load size Synthetics full load</b>	3.0	<b>Energy consumption in kWh, for program Synthetics full load</b>	1.41
<b>Programme time in minute, for program Synthetics full load</b>	65		

### Technical Data

<b>Absorbed Current (A)</b>	16	<b>Supply Frequency</b>	50
<b>Cable Length (m)</b>	1.5	<b>Supply Voltage</b>	220-240
<b>Absorbed Power (W)</b>	2300-2700	<b>Quantità di gas (kg)</b>	
<b>Plug Type</b>	Schuko		
<b>Tipo di gas</b>			

### Dimensions & Weights

<b>Package Height (cm)</b>	89.0	<b>Built-in hole Height (cm)</b>	0.0
<b>Height PF (cm)</b>	85.0	<b>Package Width (cm)</b>	64.0
<b>Built-in hole Width (cm)</b>	0.0	<b>Width PF (cm)</b>	59.5
<b>Net Weight (Kg)</b>	35.17	<b>No. Pieces per Package (Nr)</b>	1
<b>Package Weight (Kg)</b>	1.43	<b>Package Depth (cm)</b>	67.0
<b>Depth PF (cm)</b>	61.0	<b>Built-in hole Depth (cm)</b>	0.0

### Coordinated Items

<b>Life Style</b>		<b>Naming</b>	
<b>Set</b>			

### Aesthetics

<b>Door Frame colour</b>	White	<b>Frame colour</b>	
<b>Dashboard colour</b>	White	<b>Knob colour</b>	Silver
<b>Cabinet colour</b>	White	<b>Plinth colour</b>	White
<b>Door type</b>	Full Metal Door	<b>Bottle</b>	

### User Interface

<b>Dashboard graphics</b>	Text	<b>Interface</b>	Digit
<b>Dashboard graphics language</b>	Dutch (Holland) [nl-NL] , French (Holland) [fr-NL]	<b>knobs</b>	Programs Select
<b>No. of knobs</b>	1	<b>No. of buttons</b>	8
<b>No. indicators</b>	11	<b>Button/options</b>	Alarm , Delay Timer , Fast Iron , High Heat , Memo , On/Off , Start
<b>Sensing</b>	4 Level Sensing	<b>Indicators/LEDs</b>	Clean Filter , Clean condenser , Cool tumble , Dry , Empty Water Indicator , End

### Features-Programs

<b>Drying</b>	Yes	<b>End of cycle acoustic signal</b>	Yes
<b>No. Drying programmes</b>	14+2	<b>Special programs</b>	Cotton Hanger , Cotton Ready to wear , Delicates , Easy Iron , Eco Cotton , Eco Shirts , Eco Synthetics , Jeans , Outwear , Refresh , Special Shoes , Sport Light , Sportwear , Standard Cotton , Synthetics , Wool
<b>Alternate bi-directional rotation</b>	Yes	<b>Anticrease system</b>	Yes
<b>Special Features</b>	HSD	<b>Accessories</b>	

### Structural characteristics

<b>Door opening</b>	Left	<b>Water tank capacity (l)</b>	5
<b>Drum</b>	Stainless Steel	<b>Opening door diameter (cm)</b>	38
<b>Removable filter</b>	Yes	<b>Light in the drum</b>	No
<b>Reversible door</b>	No	<b>Wheels</b>	0
<b>Air Venting</b>	No	<b>Drum capacity (l)</b>	112
<b>Back of Product</b>	Legs	<b>Front of Products</b>	Legs
<b>Timer</b>	PRD36	<b>Motore</b>	Standard

### Documentation

<b>Approvals</b>	B , Ce	<b>Guarantee</b>	
<b>Booklet Languages</b>	Dutch (Holland) [nl-NL] , English (United Kingdom) [en-GB] , French (Holland) [fr-NL]	<b>R&amp;D remarks</b>	
<b>Sticker plus</b>			

### Costs

#### Marketing Remarks

Modello HSD con manopola e pulsanti silver

