

Product Information Sheet				
COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources				
Supplier's name or trade mark: PHILIPS				
Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL				
Model identifier: 9290019533				
Type of light source:				
Lighting technology used:	LED	Non-directional or directional:	DLS	
Light source cap-type (or other electric interface)	GU10			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	Only with specific dimmers	
Product parameters				
Parameter	Value	Parameter	Value	
General product parameters:				
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	5	Energy efficiency class	G	
Useful luminous flux (φ _{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	250 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2200...6500	
On-mode power (P _{on}), expressed in W	4,3	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
Outer dimensions	Height	58	Spectral power distribution in the	See image in last page
	Width	50		

without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Depth	50	range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	35	
		Chromaticity coordinates (x and y)	0,458	
Parameters for directional light sources:				
Peak luminous intensity (cd)	510	Beam angle in degrees, or the range of beam angles that can be set	42	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	0	Survival factor	0,90	
the lumen maintenance factor	0,93			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4	

(a)⚠️ : not applicable;

(b)⚠️ : not applicable;

