

| Product Information Sheet   |                          |  |                            |
|---|--------------------------|--|----------------------------|
| COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources   |                          |  |                            |
| Supplier's name or trade mark: PHILIPS  |                          |  |                            |
| Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL  |                          |  |                            |
| Model identifier: 9290019535  |                          |  |                            |
| Type of light source:   |                          |  |                            |
| Lighting technology used:   | LED                      | Non-directional or directional:  | DLS                        |
| Light source cap-type (or other electric interface)   | GU10                     |  |                            |
| Mains or non-mains:   | MLS                      | Connected light source (CLS):  | Yes                        |
| Colour-tuneable light source:   | No                       | Envelope:  | -                          |
| High luminance light source:  | No                       |  |                            |
| Anti-glare shield:  | No                       | Dimmable:  | Only with specific dimmers |
| Product parameters  |                          |  |                            |
| Parameter   | Value                    | Parameter  | Value                      |
| General product parameters:   |                          |  |                            |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer   | 6                        | Energy efficiency class  | F                          |
| Useful luminous flux (φ <sub>use</sub> ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 400 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700                      |
| On-mode power (P <sub>on</sub> ), expressed in W  | 5,2                      | Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal   | 0,00                       |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal   | 0,50                     | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80                         |
| Outer dimensions  | Height                   | Spectral power distribution in the   | See image in last page     |
|   | Width                    |  |                            |

Page 1 /

|   |       |      |  |       |
|---|-------|------|--|-------|
| without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)               | Depth | 50   | range 250 nm to 800 nm, at full-load                               |       |
| Claim of equivalent power <sup>(a)</sup>  |       | Yes  | If yes, equivalent power (W)                                       | 35    |
|   |       |      | Chromaticity coordinates (x and y)                                 | 0,458 |
| Parameters for directional light sources:   |       |      |  |       |
| Peak luminous intensity (cd)  |       | 920  | Beam angle in degrees, or the range of beam angles that can be set | 34    |
| Parameters for LED and OLED light sources:  |       |      |  |       |
| R9 colour rendering index value   |       | 0    | Survival factor  | 0,90  |
| the lumen maintenance factor  |       | 0,93 |  |       |
| Parameters for LED and OLED mains light sources:  |       |      |  |       |
| displacement factor (cos φ1)  |       | 0,50 | Colour consistency in McAdam ellipses                              | 6     |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. |       | -(b) | If yes then replacement claim (W)                                  | -     |
| Flicker metric (Pst LM)   |       | 1,0  | Stroboscopic effect metric (SVM)                                   | 0,4   |

(a)⌣ : not applicable;

(b)⌣ : not applicable;

