Data sheet for household cooker hoods In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Miele					
Model name / identifier		DA 2690			
Annual Energy Consumption					
(AEC _{hood})	kWh/year	36,2			
Energy efficiency class					
A+ (most efficient) to F (least efficient)		А			
Energy efficiency index (EEIhood)		46,4			
Fluid Dynamic Efficiency (FDE _{hood})		35,1			
Fluid Dynamic Efficiency class					
A (most efficient) to G (least efficient)		А			
Lighting Efficiency (LE _{hood})	lx/W	40,0			
Lighting Efficiency class					
A (most efficient) to G (least efficient)		А			
Grease Filtering Efficiency	%	95,3			
Grease Filtering Efficiency class					
A (most efficient) to G (least efficient)		A			
Airflow at best efficiency point	m³/h	318,1			
Air flow (min. speed)	m³/h	240			
Air flow (max. speed)	m³/h	400			
Air flow (intensive or boost setting)	m³/h	640			
Max. air flow (Q _{max})	m³/h	640			
Air pressure at best efficiency point	Pa	405			
Airborne acoustical A-weighted sound power emiss	sions				
(min. speed)	dB	42			
Airborne acoustical A-weighted sound power emiss					
(max. speed)	dB	52			
Airborne acoustical A-weighted sound power emiss					
(intensive or boost setting)	dB	63			
Electrical power input at best efficiency point	W	102,0			
Power consumption in off mode (P_0)	W	0.45			
Power consumption in standby mode (P _s)	W	0,15			
Nominal power of lighting system	W	12,0			
Average illumination of the lighting system on the c surface	ooking lx	480			
Time increase factor	IX	480 0,7			