## Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014

| Brand   | BAUMATIC |
|---|----------|
| Short Description   | BECH90X  |
| Annual Energy Consumption, AEChood (kWh/a)  | 65,4     |
| Energy Efficiency class (2010/30/EC)  | С        |
| Energy Efficiency Index, EEI  | 82,1     |
| Fluid Dynamic Efficiency (FDEhood)  | 14,7     |
| Fluid Dynamic Efficiency class  | D        |
| Lighting Efficiency (Lehood)  | 22,8     |
| Lighting Efficiency class   | В        |
| Grease Filtering Efficiency   | 78       |
| Grease Filtering Efficiency class   | С        |
| Air flow at Min/Max speed in normal use, Qmin/Qmax (m3/h)   | 524,6    |
| Air flow at at intensive or boost setting (m3/h)  | -        |
| Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A)) | 65       |
| Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A))            | -        |
| Power consumption in off mode (Po) (W)  | 0        |
| Power consumption in standby mode (Ps) (W)  | -        |
| Time increase factor, f   | 1,5      |
| Measured air flow rate at best efficiency point, QBEP (m3/h)  | 277,7    |
| Measured air pressure at best efficiency point, PBEP (Pa)   | 221      |

| Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014 |
|---|
|   |

| Measured electric power input at best efficiency point, WBEP (W)                  | 116,2 |
|---|-------|
| Nominal power of the lighting system, WL (W)                                      | 5     |
| Average illumination of the lighting system on the cooking surface, Emiddle (lux) | 114   |