

Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014

Brand	CANDY
Short Description	CBT625/2X
Annual Energy Consumption, AEChood (kWh/a)	27,5
Energy Efficiency class (2010/30/EC)	B
Energy Efficiency Index, EEI	64,7
Fluid Dynamic Efficiency (FDEhood)	13,2
Fluid Dynamic Efficiency class	D
Lighting Efficiency (Lehood)	31,8
Lighting Efficiency class	A
Grease Filtering Efficiency	56,8
Grease Filtering Efficiency class	E
Air flow at Min/Max speed in normal use, Qmin/Qmax (m3/h)	209,2/332,1
Air flow at at intensive or boost setting (m3/h)	-
Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))	56/62
Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A))	-
Power consumption in off mode (Po) (W)	0
Power consumption in standby mode (Ps) (W)	-
Time increase factor, f	1,5
Measured air flow rate at best efficiency point, QBEP (m3/h)	159
Measured air pressure at best efficiency point, PBEP (Pa)	150

Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014

**Measured electric power input at best efficiency point,
WBEP (W)** **46,9**

Nominal power of the lighting system, WL (W) **2,5**

**Average illumination of the lighting system on the cooking
surface, E_{middle} (lux)** **80**