

Energy Efficiency Information				
Attribute	Symbol	Value		Units
Model Identification		CCA52	CCA72	
Annual Energy Consumption	AEC <sub>Hood</sub>	26.5	26.5	kWh
Time increase factor	f	1.7	1.7	
Fluid Dynamic Efficiency	FDE <sub>Hood</sub>	9.4	9.4	
Energy Efficiency Index	EEl <sub>Hood</sub>	69.0	69.0	
Measured airflow at Best Efficiency Point	Q <sub>BEP</sub>	94.7	94.7	m <sup>3</sup> /h
Measured Pressure at Best Efficiency Point	P <sub>BEP</sub>	136	136	Pa
Maximum airflow	Q <sub>MAX</sub>	206.4	206.4	m <sup>3</sup> /h
Measured electric power at Best Efficiency Point	W <sub>BEP</sub>	38.0	38.0	W
Nominal lighting power	WL	4.0	4.0	W
Average illumination of the lighting system on the cooking surface	E <sub>Middle</sub>	309	309	Lux
Measured power consumption in standby	P <sub>S</sub>	N/A	N/A	W
Measured power consumption off mode	P <sub>O</sub>	0.0	0.0	W
Sound power level	L <sub>WA</sub>	63	63	dBA
Grease Filter Efficiency	GFE <sub>Hood</sub>	49.1 (F)	49.1 (F)	%
Lamp efficiency	LE <sub>Hood</sub>	77 (A)	77 (A)	%

E & O E. All instructions, dimensions and illustrations are provided for guidance only. CDA reserve the right to change specifications without prior notice.