

Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014

| | |
|--|-------------------|
| Brand | CANDY |
| Short Description | CCE1104/1X |
| Annual Energy Consumption, AEChood (kWh/a) | 37 |
| Energy Efficiency class (2010/30/EC) | C |
| Energy Efficiency Index, EEI | 76,9 |
| Fluid Dynamic Efficiency (FDEhood) | 9,5 |
| Fluid Dynamic Efficiency class | E |
| Lighting Efficiency (Lehood) | 29 |
| Lighting Efficiency class | A |
| Grease Filtering Efficiency | 79,6 |
| Grease Filtering Efficiency class | C |
| Air flow at Min/Max speed in normal use, Qmin/Qmax (m3/h) | 142/298 |
| Air flow at at intensive or boost setting (m3/h) | - |
| Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A)) | 56/63 |
| Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A)) | - |
| Power consumption in off mode (Po) (W) | 0 |
| Power consumption in standby mode (Ps) (W) | - |
| Time increase factor, f | 1,7 |
| Measured air flow rate at best efficiency point, QBEP (m3/h) | 162,9 |
| Measured air pressure at best efficiency point, PBEP (Pa) | 115 |

Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014

**Measured electric power input at best efficiency point,
WBEP (W)** **54,8**

Nominal power of the lighting system, WL (W) **4**

**Average illumination of the lighting system on the cooking
surface, E_{middle} (lux)** **157**