## Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014

Brand	CANDY
Short Description	CCE119/1N
Annual Energy Consumption, AEChood (kWh/a)	37
Energy Efficiency class (2010/30/EC)	С
Energy Efficiency Index, EEI	76,9
Fluid Dynamic Efficiency (FDEhood)	9,5
Fluid Dynamic Efficiency class	E
Lighting Efficiency (Lehood)	29
Lighting Efficiency class	A
Grease Filtering Efficiency	79,6
Grease Filtering Efficiency class	С
Air flow at Min/Max speed in normal use, Qmin/Qmax (m3/h)	142/298
Air flow at at intensive or boost setting (m3/h)	-
Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))	63
Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A))	-
Power consumption in off mode (Po) (W)	0
Power consumption in standby mode (Ps) (W)	-
Time increase factor, f	1,7
Measured air flow rate at best efficiency point, QBEP (m3/h)	162,9
Measured air pressure at best efficiency point, PBEP (Pa)	115

Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014	

Measured electric power input at best efficiency point, WBEP (W)	54,8
Nominal power of the lighting system, WL (W)	4
Average illumination of the lighting system on the cooking surface, Emiddle (lux)	157