

Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014

Brand	CANDY
Short Description	CGM64/1N
Annual Energy Consumption, AEC_{hood} (kWh/a)	49,7
Energy Efficiency class (2010/30/EC)	C
Energy Efficiency Index, EEI	72,7
Fluid Dynamic Efficiency (FDE_{hood})	16,3
Fluid Dynamic Efficiency class	D
Lighting Efficiency (Le_{hood})	70,5
Lighting Efficiency class	A
Grease Filtering Efficiency	82,1
Grease Filtering Efficiency class	C
Air flow at Min/Max speed in normal use, Q_{min}/Q_{max} (m³/h)	290/456
Air flow at at intensive or boost setting (m³/h)	-
Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))	52/56
Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A))	-
Power consumption in off mode (P_o) (W)	0
Power consumption in standby mode (P_s) (W)	-
Time increase factor, f	1,4
Measured air flow rate at best efficiency point, QBEP (m³/h)	230,3
Measured air pressure at best efficiency point, PBEP (Pa)	241

Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014

**Measured electric power input at best efficiency point,
WBEP (W)** **94,5**

Nominal power of the lighting system, WL (W) **2**

**Average illumination of the lighting system on the cooking
surface, E_{middle} (lux)** **141**