## Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014

Brand	CANDY
Short Description	CGM94/1X
Annual Energy Consumption, AEChood (kWh/a)	50
Energy Efficiency class (2010/30/EC)	С
Energy Efficiency Index, EEI	72,7
Fluid Dynamic Efficiency (FDEhood)	16,3
Fluid Dynamic Efficiency class	D
Lighting Efficiency (Lehood)	40
Lighting Efficiency class	A
Grease Filtering Efficiency	82,1
Grease Filtering Efficiency class	С
Air flow at Min/Max speed in normal use, Qmin/Qmax (m3/h)	290/456
Air flow at at intensive or boost setting (m3/h)	NO
Airborne acoustical A-weighted sound power emissions at Min/Max speed available in normal use (dB(A))	58/63
Airborne acoustical A-weighted sound power emissions at intensive or boost setting (dB(A))	NO
Power consumption in off mode (Po) (W)	0
Power consumption in standby mode (Ps) (W)	-
Time increase factor, f	1,4
Measured air flow rate at best efficiency point, QBEP (m3/h)	230
Measured air pressure at best efficiency point, PBEP (Pa)	241

Product fiche pursuant to Delegated Regulation (EU) No. 65/2014 and 66/2014

Measured electric power input at best efficiency point, WBEP (W)	94,5
Nominal power of the lighting system, WL (W)	2
Average illumination of the lighting system on the cooking surface, Emiddle (lux)	160