

N 50, Wall-mounted cooker hood, 60 cm, clear glass black printed
D651HM1S2B



COOKING PASSION SINCE 1877



B

The design hood with an inclined front and high power ensures headroom while cooking.

- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ LED lighting: a clear illumination whilst cooking thanks to the energy-saving LED lights
- ✓ Reduced Noise: the low-noise motor makes it possible to listen to your own kitchen story

Features

Technical Data

Typology : Chimney
Approval certificates : CE, VDE
Length of electrical supply cord (cm) : 130
Height of product, without chimney (mm) : 323
Minimum distance above an electric hob : 450
Minimum distance above a gas hob : 600
Net weight (kg) : 19.834
Type of control : Electronic
Maximum output air extraction (m³/h) : 416
Boost position output recirculating (m³/h) : 615.0
Maximum output recirculating air (m³/h) : 409
Boost position air extraction (m³/h) : 700
Number of lights (Stck) : 2
Noise level (dB(A) re 1 pW) : 58
Diameter of air outlet (mm) : 120 / 150
Grease filter material : Washable aluminium
EAN code : 4242004258940
Connection rating (W) : 263
Current (A) : 10
Voltage (V) : 220-240
Frequency (Hz) : 50; 60
Plug type : GB plug
Installation type : Wall-mounted

Optional accessories

Z51AII1X6	Clean Air Plus recirculation kit
Z51AIROX0	Long Life recirculation kit (chimless)
Z51AISOX0	Long Life recirculation kit
Z51AIV1X6	Clean Air Plus recirc. kit (chimless)
Z51AXC1N6	Clean Air Plus recirc. kit external



4 242004 258940

N 50, Wall-mounted cooker hood, 60 cm, clear
glass black printed
D651HM1S2B



COOKING PASSION SINCE 1877

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 700 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 58 dB dB*

Features

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- easy to clean Inner frame
- Rim ventilation

Design

- Equipped with black chimney section
- Chimney hood
- For wall mounted installation
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Easy installation system
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 416 m³/h
Intensive 700 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 58 dB(A) re 1 pW
Intensive: 67 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
Extraction rate in recirculation mode:
Max. normal use: 409 m³/h
Intensive: 615 m³/h
Noise level in recirculation mode with Clean Air Plus odor filter :
Max. normal use: 65 dB(A) re 1 pW
Intensive: 75 dB(A) re 1 pW
- Power rating: 263 W
- Light Intensity: 100 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 928-1198 x 590 x 499 mm
- Dimensions recirculating (HxWxD): 988-1258 x 590 x 499 mm
- Dimensions recirculating with CleanAir module (HxWxD):
1118 x 590 x 499 mm - mounting with outer chimney
1188-1458 x 590 x 499 mm - mounting with telescopic chimney
- Blower Efficiency Class: B*
- Lighting Efficiency Class: B*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 56.6 kWh/year*

* In accordance with the EU-Regulation No 65/2014

N 50, Wall-mounted cooker hood, 60 cm, clear glass black printed
D651HM1S2B

Dimensioned drawings

