Data sheet for household cooker hoods
In acc. with delegated regulation (EU) No. 65/2014 and regulation (EU) No. 66/2014

Model name / identifier DA 2570
Annual Energy Consumption (AEC)
(AEC <sub>Haube</sub> ) kWh/year 51,7
Energy efficiency class
Based on standard test results for 24 hours. Actual energy
consumption will depend on how the appliance is used and where
it is located.
Energy efficiency index (EEI)
(EEI <sub>Haube</sub> ) 54,7
Fluid Dynamic Efficiency (FDE) (FDE <sub>Haube</sub> ) 29,5
Fluid Dynamic Efficiency class
A (most efficient) to G (least efficient)  A
Lighting Efficiency (LE) (LE <sub>Haube</sub> ) Ix/W 50,0
Lighting Efficiency class
A (most efficient) to G (least efficient)  A
Grease Filtering Efficiency
A (most efficient) to G (least efficient)
( )
Airflow at best efficiency point m³/h 335,7
Air flow (min. speed) m³/h 250
Air flow (max. speed) m <sup>3</sup> /h 360
Air flow (intensive or boost setting) m³/h 600
Max. air flow (Q) ( $Q_{max}$ ) $m^3/h$ 600
Air pressure at best efficiency point Pa 436
Airborne acoustical A-weighted sound power emissions
(min. speed) dB 47
Airborne acoustical A-weighted sound power emissions
(max. speed) dB 56
Airborne acoustical A-weighted sound power emissions (intensive or boost setting) dB 67
(intensive or boost setting) dB 67 Electrical power input at best efficiency point W 138,0
Power consumption in off mode ( $P_0$ ) W
Power consumption in standby mode (P <sub>S</sub> )  W  0,15
Nominal power of lighting system W 6.0
Average illumination of the lighting system on the cooking
surface   Ix 300
Time increase factor 0,9