

**Serie | 2, Telescopic cooker hood, 60 cm, Silver metallic DFM063W56B**



**Optional accessories**

DSZ4545 :  
DSZ4551 :

**Telescopic cooker hoods extend when in use and slide neatly away when not in operation.**

- **Silent:** maximum extractor performance with minimal noise.
- **LED illumination:** The energy-saving lighting provides bright and clear lighting for the hob area.
- An impressive extraction rate of m3/h ensures this hood will have your kitchen odour free in no time.
- Beautifully designed to provide excellent viewability when not in use

**Technical Data**

Typology :	Pull-out
Approval certificates :	CE, VDE
Length of electrical supply cord (cm) :	175
Required niche size for installation (HxWxD) :	162mm x 526.0mm x 290mm
Minimum distance above an electric hob :	430
Minimum distance above a gas hob :	650
Net weight (kg) :	8.611
Type of control :	mechanical
Number of speed settings :	2
Maximum output air extraction (m3/h) :	328
Maximum output recirculating air (m3/h) :	182
Number of lights (Stck) :	2
Noise level (dB(A) re 1 pW) :	64
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242005231942
Connection rating (W) :	93
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation type :	Built-in



4 242005 231942

## **Serie | 2, Telescopic cooker hood, 60 cm, Silver metallic DFM063W56B**

**Telescopic cooker hoods extend when in use  
and slide neatly away when not in operation.**

---

### **Features**

- Rocker switch control for extractor speeds and light
- Automatic On/Off operation when telescopic canopy is pulled out and pushed back
- Capacitor motor
- 2 power levels
- 2 x 1,5W LED
- 2 removable metal grease filter cassettes

### **Design**

- 60 cm wide
- Silver metallic lacquer
- Handle strip specification: stainless steel with logo
- Filter cover stainless steel, perforated and dishwasher safe

### **Performance**

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit (accessory) needed
- Energy Efficiency Class: C (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 328 m<sup>3</sup>/h
- Noise level according to EN 60704-2-13 at max.normal use exhaust air:64 dB(A)re 1 pW(A)re 1 pW
- Colour Temperature: 3500 K
- Light Intensity: 131 lux
- Power rating: 93 W
- Average Energy Consumption: 41.1 kWh/year\*
- Blower Efficiency Class: D\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*

### **Planning and installation information**

- Dimensions (HxWxD): 203 x 598 x 290 mm
- Built-in dimensions (HxWxD): 162 x 526 x 290 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Electrical cable length 1.75 m

*\* In accordance with the EU-Regulation No 65/2014*



**Serie | 2, Telescopic cooker hood, 60 cm,  
Silver metallic  
DFM063W56B**

