

## Energy Efficiency Information

Attribute	Symbol	Value	Units
Model identification		EKN60, EKN70 & EKN90	
Annual Energy Consumption	$AEC_{Hood}$	62.9	kWh
Time increase factor	f	1.7	
Fluid Dynamic Efficiency	$FDE_{Hood}$	9.6	
Energy Efficiency Index	$EEl_{Hood}$	89.1 (D)	
Measured airflow at Best Efficiency Point	$Q_{BEP}$	181.8	m <sup>3</sup> /h
Measured pressure at Best Efficiency Point	$P_{BEP}$	184.0	Pa
Maximum airflow	$Q_{MAX}$	336.4	m <sup>3</sup> /h
Measured electric power at Best Efficiency Point	$W_{BEP}$	96.6	W
Nominal lighting power	WL	4	W
Average illumination of the lighting system on the cooking surface	$E_{Middle}$	430	Lux
Measured power consumption in standby	$P_S$	0.7	W
Measured power consumption off mode	$P_O$	0.46	W
Sound power level	$L_{WA}$	69.0	dBA
Grease Filter Efficiency	$GFE_{Hood}$	66.4	%
Lamp Efficiency	$LE_{Hood}$	107 (A)	%

E & O E. All instructions, dimensions and illustrations are provided for guidance only. CDA reserve the right to change specifications without prior notice.