

# Customisable dishwashing. Efficient cleaning

The MaxiFlex drawer accommodates different type of utensils. From multiple cutlery sets to over-sized utensils. Flexible dividers mean every load is customisable. Flatware is kept separate from larger items and added depth increases each cycle's capacity. The ultimate in efficient, convenient cleaning.

# **Product Benefits & Features**

# Customisable space and convenient cleaning with MaxiFlex

The MaxiFlex drawer is engineered to accommodate cutlery and utensils of every size, whether large or awkwardly shaped. Flexible dividers and maximised depth mean each load is customisable. Every item is seamlessly loaded and cleaned in one go.

> Powerful dishwashing. With SatelliteClean® Experience impeccable dishwashing with SatelliteClean®. This spray arm has three-times better

coverage than the standard. Because the double rotating arm constantly changes the angle of the spray. Water reaches every corner. For a complete clean.



# Effortless cycle-setting with QuickSelect

QuickSelect offers optimal control over the dishwasher. Choose the cycle time with the slider and add extra treatments with a tap. Then the machine will do the rest. Get tailored cleaning delivered at a time that suits. And spotless dishes.

# Water reaches every corner. With the Dual Spray Arms

Ensure maximum water coverage with two spray arms. The rotating sprinklers send water jets into every corner of both the lower and upper basket, for dishwashing results you can rely on.

- Energy efficiency (2010/30/EC): A++
- Installation: FI
- Loading capacity: 10 IEC settings
  Noise level: only 44 (dB(A) re 1 pW) (2010/30/EC)
- Water and energy consumption: 9.9 l, 0.739 kWh for program Eco 50
- 7 programmes, 4 temperatures
- Dishwasher programmes: 160 Minutes, 60 Minutes, 90 Minutes, AUTO Sense, Eco, Machine Care, Quick 30 Minutes
- · ProClean Satellite Spray arm
- Text/symbol panel
- · Touch control for programs and functions selection
- Auto Off function
- · Thermo Efficient Technology
- Warm water connection up to 60°C
- · Delay start option from 1 to 24 hours
- · Remaining time indication
- · Water sensor detects the level of dirt and adjusts water consumption
- · Indications for salt and rinse aid
- SpotControl with 2 colours
- · Height adjustable upper basket, even when fully loaded
- · Upper basket with 2 Red softspikes, Foldable cup shelves, Plastic coloured handle
- · Lower basket with 2 foldable plate racks, Plastic coloured handle
- AQUA-CONTROL
- Built-in H(min/max)xWxD (mm): 820/900 x 450 x 550



# FSE72507P

| Product Specification      |  |
|----------------------------|--|
| Product Installation       | Built_In   |
| Product Typology           | Slim(45cm)   |
| Product Classification     | Performance  |
| Installation               | FI   |
| Cabinet type of            | 45 FI 10 PS SLIDING  |
| Panel colour               | Black  |
| Door colour                | None   |
| Side walls colour          | Rough zinc coated  |
| Type of timer min.         | Level 2  |
| Push button functions      | Delay start, GlassCare, On/off,<br>Program selection, Reset, XtraPower   |
| Knob/Command functionality | No   |
| Programmes number of       | 7  |
| Number of temperatures     | 4  |
| Dishwasher programs        | 160 Minutes, 60 Minutes, 90 Minutes,<br>AUTO Sense, Eco, Machine Care,<br>Quick 30 Minutes   |
| Indicator programme        | LED  |
| Indicators display         | Delay start, Remaining time, Service code  |
| Indicators other           | Beam on floor two coloured, Buzzer,<br>Delay start 1h-24h, Drying phase,<br>GlassCare, Machine Care, Program<br>selected, Rinse aid, Salt, XtraPower |
| Height total               | 818  |
|                            |  |

| Width mm                | 446                 |
|-------------------------|---------------------|
| Depth mm                | 550                 |
| Tub material            | Stainless steel     |
| Heating element type of | Interheater         |
| Inlet hose type of      | Aqua control        |
| Inlet hose length       | 150                 |
| Water supply            | Cold or hot         |
| Anti-flood device       | Floating switch     |
| Drying system           | AirDry Technology   |
| Softening regulation    | 10 steps            |
| Top spraying level      | Waterfall           |
| Lower spray arm         | Satellite spray arm |
|                         |                     |

