

ICU 3324

Bio





Comfort

•



Model classification ¹	7
Energy efficiency class	<u>A</u> *
Energy consump. in 365 days/24 h	235/0,642
Gross/net capacity	
Total gross/net capacity	284/274 litre
Fridge compartment	201/194 litre
Including Cellar-Tray	_
Freezer compartment	83/80 litre
Star coding ²	***
Temperature rise time	24 h
Freezing capacity in 24 hours	6 kg
Climate rating ³	SN-T
Airborne acoustical noise emissions	37 dB(A)
Voltage	220-240 V ~
Connection Rating	1.4 A
Fridge compartment	
Defrosting	automatic
Interior light	LED
Fruit and vegetable bins	-
Bottle shelf	-
GlassLine Door interior	Comfort
Freezer compartment	
Defrosting	manual
Interior light	-
Freezing Technology	SmartFrost
Cold storage accumulators	-
IceMaker	-
Type of appliance	
Type	
Door assembly	Door on Door
Dimensions	
Height	177,2 - 178,8 cm
Width	56 - 57 cm
Depth incl. distance from wall	min. 55 cm
Dopur mon diotarioo from waii	min. 30 din
Features	
SoftSystem	-
Operation of the control	Buttons behind the door
EAN-Nr.	4016803180289

- 1 Model classification: 7 Fridge-freezers (4-star freezer compartment)
- 2 **** freezer compartment with -18 °C or colder
- $\textbf{3} \qquad \text{Climate Ratings: } \textbf{SN} + 10^{\circ} \texttt{C} \text{ to } + 32^{\circ} \texttt{C} \qquad \textbf{N} + 16^{\circ} \texttt{C} \text{ to } + 32^{\circ} \texttt{C} \qquad \textbf{ST} + 16^{\circ} \texttt{C} \text{ to } + 38^{\circ} \texttt{C} \qquad \textbf{T} + 16^{\circ} \texttt{C} \text{ to } + 43^{\circ} \texttt{C}$
- 4 Fixed water connection 3/4" and solenoid valve (needs to be plumped in)
- 5 To achieve the indicated energy consumption level, the wall spacers provided with the appliance must be used. These increase the appliance depth by approximately 3.5 cm and 1.5 cm at BluPerformance-appliances. If the wall spacers are not used, the appliance will remain fully functional, but will have a slightly higher energy consumption level.





Subject to modification. Timestamp: 04.01.2017

(