

**"Product fiche concerning the Commission Delegated Regulation (EU) No 65/2014 of 1 October 2013 and COMMISSION REGULATION (EU) No 66/2014 of 14 January 2014"**

Supplier name or brand	SMEG
Product code	KI120XE
Annual Efficiency Consumption (AEC <sub>hood</sub> )	63.6 kWh/year
Energy efficiency class	B
Fluid Dynamic Efficiency (FDE <sub>hood</sub> )	28.7
Fluid Dynamic Efficiency class	A
Lighting Efficiency (LE <sub>hood</sub> )	70.9 lux/W
Lighting Efficiency Class	A
Grease Filtering Efficiency	83.9 %
Grease Filtering Efficiency Class	C
Air Flow at minimum speed	316 m <sup>3</sup> /h
Air flow at maximum speed	529 m <sup>3</sup> /h
Air flow at boost speed	783 m <sup>3</sup> /h
Airborne acoustical A-weighted sound Power Emission at minimum speed	48 dB(A)
Airborne acoustical A-weighted sound Power Emission at maximum speed	62 dB(A)
Airborne acoustical A-weighted sound power emission at boost speed	70 dB(A)
Power consumption in stand-by mode	0.49 W
Time increase factor	1.00
Energy Efficiency Index	59
Measured air flow rate at best efficiency point	394 m <sup>3</sup> /h
Measured air pressure at best efficiency point	449 Pa
Measured electric power input at best efficiency point	171 W
Normal Power of the light system	4 W
Average illumination of the light on the cooking surface (E <sub>middle</sub> )	312 lux
Sound power level at highest setting	62 dB(A)

23 November 2017