

Type	Technical Code
Cookers	AXOYJENAXE.00
Stato	
UnderReview	
Product family	COOKERS 90X60 CM - PREMIUM
Brand	BERTAZZONI
Make or Buy Flag	Make
Type of installation	FREE STANDING
Technical code	AXOYJENAXE.00
Commercial description	MAS9511EXC - Master FS Cookers - Induction - Inox
Short Description IT	MAS9511EXC - Master FS Cookers - Induction - Inox
Short Description EN	MAS9511EXC - Master FS Cookers - Induction - Inox
EAN Required	YES
Commercial code	MAS9511EXC
Market	EUROPE;GREAT BRITAIN
Years of warranty	2
20" Containerization	0
LeadTime	0
Combined Naming	85166010
Changes notes	
Energy Label Required	
YES	
Energy class OD	A
Natural convention energy consumption (kWh)	1,1
Main oven net capacity l	86
Required cooking time for normal load (min)	
Secondary oven energy class OD	
Natural convention energy consumption secondary oven(kWh)	
Secondary oven net capacity l	0
Required cooking time for normal load secondary oven(min)	
Heat Source	ELECTRIC
Energy consumption in conventional mode (electric final energy)[kWh] 1.1	
Energy consumption in conventional mode(gas final energy) [MJ/Cycl] 0.0	
Energy consumption in conventional mode (gas final energy)[kWh/Cy] 0.0	
Heat source secondary oven	
Energy consumption in conventional mode secondary oven (electric fi 0.0	
Energy consumption in conventional mode secondary oven (gas final 0.0	
Energy consumption in conventional mode secondary oven (gas final 0.0	
Heat source third oven	
Energy consumption in conventional mode third oven (electric final e 0.0	
Energy consumption in conventional mode third oven (gas final energ 0.0	
Energy consumption in conventional mode third oven (gas final energ 0.0	
Convention oven consumption	FES.PCX
Convention secondary oven consumption	
Main oven grilling tray surface	2030
Hob energy efficiency	
Energy Label Country	UE + UK
Technical Data	
Supply voltage [V]/Supply frequency [Hz]	220-240V~/380-415V3N~ 50/60Hz collaudo monofase
(Alternative) Supply voltage [V]/Supply frequency [Hz]	NO
Absorbed current [A]	50A
Plug type	NO
Minimum Cable length (m)	1,8
Gas type	ELECTRIC PRODUCT
Alternative gas	NO
Gas connectors	NO
Main oven max power [W]	3500.0
Main grill max power [W]	2700.0
Dimensions & Weights	
Height PF (mm)	893-913
Width PF (mm)	900
Depth PF (mm)	600
Depth with handle (mm)	658
Depth with open door (mm)	1030
Built-in hole height (mm)	
Built-in hole width (mm)	
Built-in hole depth (mm)	

Package type	FORK PALLET
Package height (mm)	1080
Package width (mm)	1006
Package depth (mm)	720
Net weight (Kg)	95.5
Gross weight (Kg)	110.0

User Interface

Type of regulation	KNOBS
Function indicator	RING

Hob characteristics

Type of hob	90X60 PREMIUM INDUCTION
Info of hob	SQUARED 5 INDUCTION ZONES DOUBLE BRIDGE
Special hob features	BOOSTER;BRIDGE;CHILD LOCK
Burner and burner cap	NO
Hob accessories	NO

Aesthetics

Fascia type	EMBOSSSED STAINLESS STEEL
Oven door glass colour	O SHAPE MAS/AMER ROUNDED CORNERS
Hinge	SOFT MOTION
Type of lid	RAISER
Handle type	MASTER 2020
Gas Tank Compartment	NO
Legs	STAINLESS STEEL Ø 6 CM TYPE A

Hob layout

No. of total cooking areas	5
No. electric plates	0
No. induction areas	5
No. Hood area	
Bridge left area - power (W)	

Rear Side

Left\$Centre\$Right

Circular cooking zone or area-diameter surface [mm] zone left-behind	
Circular cooking zone or area-diameter surface [in] zone left-behind	
Non-circular cooking zone or area-length [mm] zone left-behind	200
Non-circular cooking zone or area-length [in] zone left-behind	0.0
Non-circular cooking zone or area-width [mm] zone left-behind	210
Non-circular cooking zone or area-width [in] zone left-behind	0.0
Rear left area - type	INDUCTION
Left rear area - dimensions	200x210
Rear left area - power (W)	2100
Energy consumption [Wh/Kg] zone left-behind	
Energy efficiency per gas burners [%] zone left-behind	
Electricity consumption left-behind	175
Rear left area - power booster [W]	3000
Rear left area - double power booster [W]	

Front Side**Left\$Centre\$Right**

Circular cooking zone or area-diameter surface [mm] zone left-ahead	
Circular cooking zone or area-diameter surface [in] zone left-ahead	
Non-circular cooking zone or area-length [mm] zone left-ahead	200
Non-circular cooking zone or area-length [in] zone left-ahead	0.0
Non-circular cooking zone or area-width [mm] zone left-ahead	210
Non-circular cooking zone or area-width [in] zone left-ahead	0.0
Left front area - type	INDUCTION
Left front area - dimensions	200x210
Front left area - power (W)	1600
Energy consumption [Wh/Kg] zone left-ahead	
Energy efficiency per gas burners [%] zone left-ahead	
Electricity consumption left-ahead	175
Total electricity consumption	175
Front left area - power booster [W]	1850
Front left area - double power booster [W]	

Main Oven

Oven cavity	90X60 PREMIUM WELDED
Cooking modes 1	BAKE;BOTTOM BAKE;CONVECTION (ELECTRIC OVENS);CONVECTION BAKE;DE
Cleaning	NO
Light turning on	2
Type of main oven guides	LATERALS GRIDS
Gross volume oven	105.0
Net oven volume	79.0
Oven grids	2 PREMIUM
Oven grill tray	1 ENAMELED + 1 GRID TRAY

Secondary Oven

Secondary oven type/Secondary grill	NO
Cooking modes 2	
Secondary oven cleaning	NO
Secondary oven turnspit	NO
Matériau de la cavité du four secondaire	NO
Gross volume secondary oven	0.0
Net volume secondary oven	0.0
Grids of the secondary oven	NO
Oven gasket 2	NO

Third Oven

Third oven type/Third Grill	NO
Type of third oven guides	NO
Gross volume third oven	0.0
Net volume third oven	0.0
Third oven accessories	NO

Safety devices

Hob ignition	NO
Cooling fan	YES
No. residual heat indicators	YES

Documentation

Booklet languages	ENGLISH
Annual energy consumption - AEC hood (kWh/annum)	
Fluid dynamic efficiency class	
Power consumption off mode - Po (W)	

Grease filtering efficiency - GFEhood (%)

Odor reduction Factor of (%)

Maximum air flow in normal use (Intensive / Boost excluded) (m³/h)

Average illumination of the lighting system on the cooking surface - E_a

Max air flow (m³/h)

Output air extraction (m³/h)

Sound power level at Intensive/Boost Setting - (dB(A) re 1Pw)

Fan power [W]

Type of hood

Filter type

Special features hoods

Commercial Code

MAS95I1EXC F004920

General Information

Life Cycle Y2 - On Management
Aesthetical line MASTER
Private Label BERTAZZONI
Type of production CBU
Factory Guastalla
Predecessor Code AXOYJEMANE.00

Short Description FR MAS95I1EXC - Master FS Cookers - Induction - Inox
Short Description US
Ean code 8059304886119
Second commercial code
Customer GENERICO
Approvals CE;UKCA
40" Containerization 0
MOQ of purchase 0
Notes

Energy Label

Number of cavities 1
Oven program used to determin FAST.PCX
Forced convention energy consu 0,87
Oven typology energy label BIG (65L < = VOLUME)

Oven program used to determin
Forced convention energy consu
Oven typology energy label seco

EEI [%]Energy efficiency index 95.6
Energy consumption in fan force 0.87
Energy consumption in fan force 0.0
Energy consumption in fan force 0.0
EEI [%]energy efficiency index s 0.0
Energy consumption in fan force 0.0
Energy consumption in fan force 0.0
Energy consumption in fan force 0.0
EEI [%]Energy efficiency index tl 0.0
Energy consumption in fan force 0.0
Energy consumption in fan force 0.0
Energy consumption in fan force 0.0
Fan-assisted oven consumption FAST.PCX
Fan-assisted secondary oven cor
Secondary oven grilling tray surf
Heating technology induction

Absorbed power [W] 10900
(Alternative) Absorbed power [W] N.A.
Gas power [kW] 0.0

Minimum Cable length (in) 71"

Alternative gas NO

Secondary oven max power [W] 0.0

Secondary grill max power [W] 0.0

Height PF (in) 0

Width PF (in)

Depth PF (in)

Depth with handle (in)

Depth with open door (in)

Built-in hole height (in)

Built-in hole width (in)

Built-in hole depth (in)

Package height (in)	42 1/2
Package width (in)	39 5/8
Package depth (in)	28 1/8
Net weight (Lb)	0.0
Gross weight (Lb)	0.0

Type of regulation	THERMOMETER
Cooking control functions	CHECK PREHEATING

MC_05-PowerLimitation

Cooking Zone	ELECTRIC
Hob material	STAINLESS STEEL
Pan support type	NO

Inner door	SQUARED 3 GLASSES
Side panel colour	STAINLESS STEEL
Knob type	MASTER METAL WITH RING 2020
Dish warmer	FLAP STAINLESS STEEL
Plinth	NO

No. gas burners	0
No. of radiant areas	0
No. dishwarmer areas	0
No. of bridge induction areas	
Bridge right area - power (W)	

Circular cooking zone or area-di
Circular cooking zone or area-di
Non-circular cooking zone or area
Non-circular cooking zone or area: 0.0
Non-circular cooking zone or area
Non-circular cooking zone or area: 0.0
Rear middle area - type
Middle rear area - dimensions
Rear middle area - power (W)
Energy consumption [Wh/Kg] zc
Energy efficiency per gas burner
Electricity consumption center-t
Rear middle area - power boost
Rear middle area - double power

Circular cooking zone or area-di: 265
Circular cooking zone or area-di
Non-circular cooking zone or area
Non-circular cooking zone or area: 0.0
Non-circular cooking zone or area
Non-circular cooking zone or area: 0.0
Middle front area - type INDUCTION
Middle front area - dimensions 265
Middle front area - power (W) 2300
Energy consumption [Wh/Kg] zc
Energy efficiency per gas burner
Electricity consumption center-a 175

Front middle area - power boost 3000
Front middle area - double power

Main oven type/main grill CONVECTION ELECTRIC OVEN MULTI 9/MULTI11

Cleaning functions 1

Turnspit/Fans 1 FAN
Main cavity material BLACK ENAMELED

Gross volume oven [cu.ft]

Net volume oven [cu.ft]
Main oven accessories 1 EXTRACTION HANDLE
Oven gasket 4 SIDES

Cleaning functions 2

Secondary oven light turning on NO
Type of secondary oven guides NO
Gross volume secondary oven [c
Net volume secondary oven [cu.
Secondary oven accessories NO
Oven grill tray 2 NO

Cooking modes 3

Grids of the third oven NO
Gross volume third oven [cu.ft]
Net volume third oven [cu.ft]
Oven grill tray 3 NO

Hob flame failure device NO
Anti-tilt YES + CHAIN
Knob deflector NO

Warranty certificate NO

Energy efficiency class
Lighting efficiency class
Power consumption in standby m

Light efficiency - LEhood (Lux/W)
Fluid dynamic efficiency - FDEhood
Minimum air flow in normal use
Energy efficiency index - EEIhood
IEC extraction (m³/h)
Measured electric power input at
Sound power level at minimum :
Measured air pressure at best ef
Hood control
Hood accessories
Child lock

Code

Colour leading code

STAINLESS STEEL

Technical code of derivation

Approval code

40" Containerization - High cube

0

MOQ of selling

0

[Redacted]

[Redacted]

[Redacted]

[Redacted]

No. of total electric cooking areas	5
No. halogen areas	0
MC_05-NbruciatoriWok	

[Redacted]

Circular cooking zone or area-diameter surface [mm] zone right-behind	
Circular cooking zone or area-diameter surface [in] zone right-behind	
Non-circular cooking zone or area-length [mm] zone right-behind	200
Non-circular cooking zone or area-length [in] zone right-behind	0.0
Non-circular cooking zone or area-width [mm] zone right-behind	210
Non-circular cooking zone or area-width [in] zone right-behind	0.0
Rear right area - type	INDUCTION
Right rear area - dimensions	200x210
Right rear area - power (W)	2100
Energy consumption [Wh/Kg] zone right-behind	
Energy efficiency per gas burners [%] zone right-behind	
Electricity consumption right-behind	175
Rear right area - power booster [W]	3000
Rear right area - double power booster [W]	

Circular cooking zone or area-diameter surface [mm] zone right-ahead	
Circular cooking zone or area-diameter surface [in] zone right-ahead	
Non-circular cooking zone or area-length [mm] zone right-ahead	200
Non-circular cooking zone or area-length [in] zone right-ahead	0.0
Non-circular cooking zone or area-width [mm] zone right-ahead	210
Non-circular cooking zone or area-width [in] zone right-ahead	0.0
Front right area - type	INDUCTION
Right front area - dimensions	200x210
Front right area - power (W)	1600
Energy consumption [Wh/Kg] zone right-ahead	
Energy efficiency per gas burners [%] zone right-ahead	
Electricity consumption right-ahead	175
Front right area - power booster [W]	1850
Front right area - double power booster [W]	

Grease filtering efficiency class

Air flow at intensive/Boost setting - (m³/h)

Increase factor

Measured air flow rate at best efficiency point - Q_{bep} (m³/h)

Nominal power consumption of the lighting system - W_l (W)

Sound power level at maximum speed available in normal use - (dB(A) re 1Pw)

Sound level maximum speed (dbA)

Speed

██████████

██████████

████████

████████

████████

████████

████████

██████████

██████████

██████████

██████████

██████████

██████████

██████████

██████████