Appliance status: R Valid from: 16. 02. 2021 Last modification: 26. 03. 2021 02:32:58

PRODUCT FICHE

Built-In Oven

738509



738509 BI62212AXUK	
USP :	
Door type	Double glazed oven door with one heat deflector (CompactDoor)
Multiphase Cooking	× · · · · ·
Door hinge	Classic door hinge
Oven type	Fan oven BigSpace - 77 I SuperSize baking area
Maximum oven temperature	300 °C
Cooling fan	Dynamic oven cooling plus - DC+
Super Size	×
Even Bake	This advanced technology is why your cooking is always on point. Everything you put in this oven is cooked evenly thanks to slightly rounded large cavity which together with smartly positioned special heaters enables excellent and even hot air distribution. This means crispy on the outside, juicy on the inside. Big glass door and great inside illumination enable you to check on your food anytime without opening the door and letting out hot air. Efficient and even cooking guaranteed.
Gentle Bake	×
Fast Preheat	With this Fast Preheat you can start your cooking earlier. The oven reaches a temperature of up to 200°C in less than 5 minutes, which is much faster than standard preheating. This is very convenient for recipes that require a preheated oven. A light and sound signal informs your when the desired temperature is reached.
Large infra heater	×
Frozen Bake Mode	This function is perfect for cooking your store -bought frozen foods and other pre-prepared meals such as croissants, lasagne, French fries, chicken nuggets and other pre-baked frozen meat cuts and vegetables. Your dinner will be ready quickly, without preheating.
Interior light	Above
Pizza Mode	Now you can enjoy your homemade pizza whenever. Maximum temperature of 300 degree and excellent heat distribution allow that pizza is baked in a very short time tasting just as delicious it would in any Italian restaurant.
Auto Programs	All you need to know is your ingredients and this oven will do the rest. According to the weight of your dish it will set the right temperature, turn on the heaters and calculate the cooking time. Without complaining. And with the best possible result. You can choose out of 22 automatic programs and put your mind to rest. Cook like a rookie, and with auto programs, eat like a pro.
Gratin	If you want your food all beautiful and crispy, we have a solution for you. Activate gratin function so the grill heater from above will deliver extremely high heat close to the surface of your food. Perfect crust is now just a touch away.
Pro Grill	×
Extra Durable Enamel	4
	•

BrandHISENSECommercial codeBI62212AULKInternal article number738509EAN code333782510892Main colour of productV2065; Brushed stainless steelConstruction typeBuilt-InType of controlMechanicalMicroware functionNoAre any hobs controls integrated?YeesDoor MaterialGlassEnergy inputN/AConstruction traingOWConstruction ratingOWCourrent0,0 AVoltageN/AFrequencyN/AVoltageN/AFrequencyN/AVoltageS95 mmPlug type for ductS95 mmVidth of the productS95 mmVidth of the productS95 mmVidth of the productS95 mmVidth of the productS90 mmVidth of the packed productS60 mmVidth of the packed productS90 mmMax height of installation nicheS00 mmMax height of installation n	Product group	Built-In Oven
Internal article number738509EAN code3833782510892Main colour of productVZ065; Brushed stainless steelConstruction typeBullt-inType of controlMechanicalMicrowave functionNoAre any hobs controls integrated?YesDoor MaterialGlassEnergy inputN/AConstruction ratingO WElectrical connection ratingO WElectrical connection ratingO WCurrent0,0 AVoltageN/AFrequencyN/AMarks of conformityCELength of helectrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWith of the product600 mmWith of the product596 mmWith of the product600 mmMin theight of installation niche600 mmMax with of installation niche500 mmCool / Material front20.6 kgCool / Material front20.6 k	Brand	HISENSE
EAN code3888782510892Main colour of productVZ065; Brushed stainless steelConstruction typeBuilt-InType of controlMechanicalMicrowave functionNoAre any hobs controls integrated?YesDoor MaterialGlassEnergy inputN/ACooking methodFanGas connection rating0 WElectrical connection rating0,0 AVoltageN/AFrequencyN/AVoltageS95 mmHeight of the product595 mmHeight of the product595 mmVitto of the packed product660 mmWith of the packed product620 mmMin height of installation niche590 mmMan height of installation niche590 mmMark with of installation niche590 mmColor / Material from700 mmColor / Material from700 mmColor / Material from500 mmColor / Material from500 mmColor / Material from500 mm	Commercial code	BI62212AXUK
Main colour of productVZ065; Brushed stainless steelConstruction typeBuilt-inType of cortolMechanicalMicrowave functionNoAre any hobs controls integrated?YesDoor MaterialGlassEnergy inputN/ACooking methodFanGasconnection rating0 WElectrical connection rating0 WCurrent0,0 AVoltageN/AFrequencyN/AVoltageN/AFrequencyN/AUp type for the product595 mmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmDepth of the product600 mmWith of the product600 mmWith of the product600 mmWith of the packed product600 mmMin height of installation niche500 mmMax with of installation niche500 mmAutomatic programmes500 KgAutomatic programmes500 KgColor / Material front500 Kg	Internal article number	738509
Construction typeBuilt-InType of controlMechanicalMicroware functionNoAre any hobs controls integrated?YesDoor MaterialGlassDoor MaterialN/ACooking methodFanCooking methodFanCooking methodOWElectrical connection ratingOWCurrent0,0 AVotageN/AConformityCELength of electrical supply cord150 cmVotageWithout plug, supply cord 3 x 1.5Height of the product595 mmVight of the product595 mmWithout plug supply cord 3 x 1.5Height of the product660 mmWidth of the product660 mmWidth of the packed product660 mmWidth of installation niche590 mmMax height of installation niche560 mmCor / Material front20.0 KgAutomatic pr	EAN code	3838782510892
Type of controlMechanicalMicrowave functionNoAre any holos controls integrated?YesDoor MaterialGlassEnergy inputN/ACooking methodFanGas connection rating0 WElectrical connection rating0 WCurrent0,0 AVoltageN/AFrequencyN/AMarks of conformityCELength of electrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmVoltage595 mmVith of the product595 mmDepth of installation niche590 mmMax hight of installation niche500 mmMax hight of installation niche564 mmMax hight of installation niche560 mmMix width of installation niche564 mmMax width of installation niche560 mmMax width of installation niche560 mmMax width of installation niche564 mmMax width of installation niche560 mmMax width of installation niche	Main colour of product	VZ065; Brushed stainless steel
Microwave functionNoAre any hobs controls integrated?YesDoor MaterialGlasssEnergy inputN/ACooking methodFanCooking method0 WCooking method0 WElectrical connection rating0 WCurrent0,0 AVoltageN/AFrequencyN/AMarks of conformityCELength of electrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWitht of the product595 mmWitht of the product600 mmWitht of the product600 mmWitht of installation niche600 mmMark if installation niche500 mmMin with of installation niche500 mmMax height of installation niche500 mmMax with of installation niche500 mmMork of installation niche500 mmMax height of installation niche500 mmCord / Material Font31.0 KgCord / Material Font20.0 Kg	Construction type	Built-in
Are any hobs controls integrated?YesDor MaterialGlassEnergy inputN/ACooking methodFanGas connection rating0 WElectrical connection rating0 WCurrent0,0 AVoltageN/AFrequencyN/AVoltage of conformityCELength of electrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWidth of the product595 mmWidth of the product660 mmWidth of the packed product660 mmWidth of installation niche590 mmMax holf of installation niche560 mmMax width of installation niche560 mmMax width of installation niche550 mmColor / Material font29.0 KgGross weight31,0 KgAutomatic programmesNA <tr <td="">Color / Material font<</tr>	Type of control	Mechanical
Door MaterialGlassEnergy inputN/ACooking methodFanCooking methodGas connection ratingCurrent0.0 WCurrent0.0 AVoltageN/AFrequencyN/AMarks of conformityCELength of electrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmVoltade595 mmWithout full of the product660 mmWith of the packed product620 mmWith of the packed product590 mmMin height of installation niche590 mmMax width of installation niche560 mmMax width of installation niche560 mmMax width of installation niche500 mmNatingt of installation niche500 mmColor / Material front7205; Brushed stainless steel	Microwave function	No
Energy inputN/ACooking methodFenGas connection rating0 WElectrical connection rating0 WCurrent0,0 AVoltageN/AFrequencyN/AMarks of conformityCELength of electrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmDepth of the product595 mmWidth of the product660 mmWidth of the packed product660 mmWidth of installation niche590 mmMax height of installation niche500 mmMax width of installation niche560 mmMax width of installation niche500 mmNat weight29,0 KgGross weight31,0 KgAutomatic InfortVZ065; Brushed stainless steel	Are any hobs controls integrated?	Yes
Cooking methodFanGas connection rating0 WElectrical connection rating0 WCurrent0,0 AVoltageN/AFrequencyN/AMarks of conformityCELength of electrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmDepth of the product584 mmHeight of the product660 mmWidth of the packed product660 mmWidth of installation niche590 mmMax widt of installation niche590 mmMax width of installation niche560 mmMax width of installation niche550 mmDepth of installation niche550 mmDepth of installation niche550 mmMax width of installation niche550 mmDepth of installation ni	Door Material	Glass
Gas connection rating0 WElectrical connection rating0 WCurrent0,0 AVoltage0,0 AYoltageN/AFrequencyN/AMarks of conformityCELength of electrical supply cord 3 x 1.5Plug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmVoltage595 mmWidth of the product660 mmDepth of the packed product660 mmWidth of the packed product675 mmWidth of installation niche590 mmMax height of installation niche500 mmMax width of installation niche564 mmMax width of installation niche500 mmNaterial front31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Energy input	N/A
Electrical connection rating0 WCurrent0,0 AVoltageN/AFrequencyN/AMarks of conformityCELength of electrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmDepth of the product595 mmDepth of the packed product660 mmWidth of the packed product675 mmMin height of installation niche590 mmMax widt of installation niche564 mmMin width of installation niche560 mmMax widt of installation niche560 mmMax width of installation niche560 mmMax width of installation niche560 mmMax wight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stalness steel	Cooking method	Fan
Current0,0 AVoltageN/AVoltageN/AFrequencyN/AMarks of conformityCELength of electrical supply cord 3 x 1.5Plug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWith of the product595 mmWidth of the product660 mmWidth of the packed product660 mmWidth of the packed product620 mmDepth of the packed product675 mmMin height of installation niche590 mmMax height of installation niche560 mmMax width of installation niche560 mmNet weight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Gas connection rating	0 W
VoltageNAFrequencyN/AMarks of conformityCELength of electrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWidth of the product595 mmDepth of the product595 mmWidth of the packed product660 mmWidth of the packed product620 mmDepth of the packed product600 mmMin width of installation niche590 mmMax width of installation niche500 mmMax width of installation niche564 mmDepth of installation niche500 mmMax width of installation niche500 mmDepth of installation niche500 mmMax width of installation niche500 mmMax width of installation niche500 mmDepth of installation niche500 mmDepth of installation niche500 mmDepth of installation niche500 mmMax width of installation niche500 mmDepth of installation niche500 mmNet weight31,0 KgColor / Material frontVZ065; Brushed stainless steel <td>Electrical connection rating</td> <td>0 W</td>	Electrical connection rating	0 W
FrequencyN/AMarks of conformityCELength of clectrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWidth of the product595 mmDepth of the product564 mmHeight of the packed product660 mmWidth of in the packed product620 mmDepth of installation niche590 mmMax height of installation niche500 mmMax width of installation niche560 mmMax width of installation niche560 mmMax width of installation niche560 mmMax width of installation niche500 mmNet weight29,0 KgGross weight1,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Current	0,0 A
FrequencyN/AMarks of conformityCELength of clectrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWidth of the product595 mmDepth of the product564 mmHeight of the packed product660 mmWidth of in the packed product620 mmDepth of installation niche590 mmMax height of installation niche500 mmMax width of installation niche560 mmMax width of installation niche560 mmMax width of installation niche560 mmMax width of installation niche500 mmNet weight29,0 KgGross weight1,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Voltage	N/A
Length of electrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWidth of the product595 mmDepth of the product564 mmHeight of the packed product660 mmWidth of the packed product620 mmDepth of the packed product675 mmMin height of installation niche590 mmMax height of installation niche500 mmMax width of installation niche560 mmMax width of installation niche500 mmMax width of installation niche500 mmMax width of installation niche500 mmDepth of installation niche500 mmMat width of installation niche500 mmNet weight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel		N/A
Plug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWidth of the product595 mmDepth of the product564 mmHeight of the packed product660 mmWidth of the packed product620 mmDepth of the packed product675 mmDepth of the packed product675 mmMin height of installation niche590 mmMax height of installation niche600 mmMax width of installation niche560 mmMax width of installation niche564 mmDepth of installation niche560 mmMax width of installation niche564 mmDepth of installation niche564 mmMax width of installation niche560 mmMax width of installation niche560 mmMax width of installation niche500 mmMax width of installation niche500 mmMax width of installation niche560 mmMax width of installation niche500 mmMaterial fron tiche29,0 KgGross weight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Marks of conformity	CE
Height of the product595 mmWidth of the product595 mmDepth of the product564 mmHeight of the packed product660 mmWidth of the packed product620 mmDepth of the packed product675 mmDepth of the packed product675 mmMin height of installation niche590 mmMax height of installation niche600 mmMin width of installation niche560 mmMax width of installation niche560 mmMax width of installation niche560 mmMax width of installation niche564 mmDepth of installation niche550 mmMax width of installation niche500 mmNet weight29,0 KgGross weight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Length of electrical supply cord	150 cm
Width of the product595 mmDepth of the product564 mmHeight of the packed product660 mmWidth of the packed product620 mmDepth of the packed product675 mmMin height of installation niche590 mmMax height of installation niche600 mmMin width of installation niche560 mmMax width of installation niche560 mmDepth of installation niche560 mmMax width of installation niche560 mmMax width of installation niche560 mmMax width of installation niche560 mmDepth of installation niche560 mmNet weight29,0 KgGross weight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Plug type	Without plug, supply cord 3 x 1.5
Depth of the product564 mmHeight of the packed product660 mmWidth of the packed product620 mmDepth of the packed product675 mmMin height of installation niche590 mmMax height of installation niche600 mmMin width of installation niche560 mmMax width of installation niche560 mmDepth of installation niche550 mmMax width of installation niche550 mmDepth of installation niche550 mmDepth of installation niche550 mmDepth of installation niche550 mmDepth of installation niche550 mmNet weight29,0 KgGross weight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Height of the product	595 mm
Height of the packed product660 mmWidth of the packed product620 mmDepth of the packed product675 mmMin height of installation niche590 mmMax height of installation niche600 mmMin width of installation niche560 mmMax width of installation niche560 mmMax width of installation niche564 mmDepth of installation niche550 mmMax width of installation niche550 mmMax width of installation niche550 mmDepth of installation niche550 mmDepth of installation niche550 mmNet weight29,0 KgGross weight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Width of the product	595 mm
Width of the packed product620 mmDepth of the packed product675 mmMin height of installation niche590 mmMax height of installation niche600 mmMin width of installation niche560 mmMax width of installation niche564 mmDepth of installation niche550 mmMax width of installation niche550 mmDepth of installation niche550 mmDepth of installation niche550 mmDepth of installation niche550 mmDepth of installation niche550 mmNet weight29,0 KgGross weight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Depth of the product	564 mm
Depth of the packed product675 mmMin height of installation niche590 mmMax height of installation niche600 mmMin width of installation niche560 mmMax width of installation niche564 mmDepth of installation niche550 mmNet weight29,0 KgGross weight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Height of the packed product	660 mm
Min height of installation niche590 mmMax height of installation niche600 mmMin width of installation niche560 mmMax width of installation niche564 mmDepth of installation niche550 mmNet weight29,0 KgGross weight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Width of the packed product	620 mm
Max height of installation niche600 mmMin width of installation niche560 mmMax width of installation niche564 mmDepth of installation niche550 mmNet weight29,0 KgGross weight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Depth of the packed product	675 mm
Min width of installation niche560 mmMax width of installation niche564 mmDepth of installation niche550 mmNet weight29,0 KgGross weight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Min height of installation niche	590 mm
Max width of installation niche564 mmDepth of installation niche550 mmNet weight29,0 KgGross weight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Max height of installation niche	600 mm
Depth of installation niche550 mmNet weight29,0 KgGross weight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Min width of installation niche	560 mm
Net weight29,0 KgGross weight31,0 KgAutomatic programmesN/AColor / Material frontVZ065; Brushed stainless steel	Max width of installation niche	564 mm
Gross weight 31,0 Kg Automatic programmes N/A Color / Material front VZ065; Brushed stainless steel	Depth of installation niche	550 mm
Automatic programmes N/A Color / Material front VZ065; Brushed stainless steel	Net weight	29,0 Kg
Color / Material front VZ065; Brushed stainless steel	Gross weight	31,0 Kg
······································	Automatic programmes	N/A
Grill power 0W	Color / Material front	VZ065; Brushed stainless steel
	Grill power	0 W

Features :

Temperature control	N/A
Short description of the product	BO3CO3C02-1 - BI62212AXUK - RL_ESSL
Timer	N/A
Integrated Cleaning system	Easy to clean enamel
Grids	2
Time control	No control of the time
Time-setting Options	No delay option
Trays	1
Control panel information	N/A
Oven interior	Enamelled steel
Motorized Turn Spit	N/A
Additional equipment included	Deep baking pan - 1 Oven grid - 2
Safety device	Thermo electric oven protection
Oven lighting	Yes
Position of interior lights	N/A
Meat probe	No
Oven guides	Wire type 1x
Energy (lebel information / Derformance :	

49.3 min 51.5 min

77 I 1 0,00 0,0 N/A

1,0 W 0,0 kWh/Zyklus 0,0 Mj 0,0 kWh/cycle

Energy label information / Performance :

Standard load cooking time - fan cooking	
Standard load cooking time - conventional cooking	
The power consumption in off-mode	
Energy consumption per cycle conventional (2010/30/ES)	
Energy consumption gas oven per cycle conventional (2010/30/ES)	
Energy consumption per cycle forced air convection (2010/30/ES)	
Usable volume of cavity (2010/30/ES)	
Number of cavities - NEW (2010/30/EC)	
Energy consumption gas oven per cycle conventional - NEW (2010/30/EC)	
Energy efficiency index (2010/30/EC)	
Energy efficiency class	

Energy consumption conventional Noise Energy consumption forced air convection Useable volume (of cavity) Product size 0,0 kWh 42 db(A)re 1 pW 0,0 kWh 77 l Large

