

## Energy Efficiency Information

Attribute	Symbol	Value			Units
Model Identification		ECN62/72/92	ECP62/72/92	ECP92/102/112	
Annual Energy Consumption	AEC <sub>Hood</sub>	60	60	60	kWh
Time increase factor	f	1.7	1.7	1.7	
Fluid Dynamic Efficiency	FDE <sub>Hood</sub>	9.7	9.7	9.1	
Energy Efficiency Index	EEl <sub>Hood</sub>	88.1	88.1	88.1	
Measured airflow at Best Efficiency Point	Q <sub>BEP</sub>	227.7	227.7	219.2	m <sup>3</sup> /h
Measured Pressure at Best Efficiency Point	P <sub>BEP</sub>	141.0	141.0	137.0	Pa
Maximum airflow	Q <sub>MAX</sub>	390.8	390.8	377.2	m <sup>3</sup> /h
Measured electric power at Best Efficiency Point	W <sub>BEP</sub>	92.2	92.2	91.61	W
Nominal lighting power	WL	4	4	4	W
Average illumination of the lighting system on the cooking surface	E <sub>Middle</sub>	540	540	540	Lux
Measured power consumption in standby	P <sub>S</sub>	N/A	N/A	N/A	W
Measured power consumption off mode	P <sub>O</sub>	0.0	0.0	0.0	W
Sound power level	L <sub>WA</sub>	60.0	60.0	60.0	dBA
Grease Filter Efficiency	GFE <sub>Hood</sub>	71.4 (D)	71.4 (D)	76.7 (C)	%
Lamp efficiency	LE <sub>Hood</sub>	135 (A)	135 (A)	135 (A)	%

E & O E. All instructions, dimensions and illustrations are provided for guidance only. CDA reserve the right to change specifications without prior notice.