

PRODUCT FICHE

Hisense



Kitchen hood 738941 CH6C4BXUK

USP :

Motor type	Capacitor motor
Number of speed positions	3
Number of lights	2
Lamp type	LED
Illumination setting	On/off light switch
Number of filters	2
Filter material	Aluminium
Washable grease filter	✔
Odour filter	Optional
Air flow by extraction version, step 1	252 m³/h
Air flow by extraction version, step 2	354 m³/h
Maximum extraction rate by extraction operation	450 m³/h
Noise level (min.)	56 dB(A)re 1 pW
Max. noise level	65 dB(A)re 1 pW

Basic information :

Product group	Kitchen hood
Decor panel options	N/A
Construction type	Free-standing
Brand	HISENSE
Product name / Family	Kitchen hood
Commercial code	CH6C4BXUK
Internal article number	738941
EAN code	3838782525711
Color body	Inox
Material body	Stainless steel
Color chimney	Inox
Material chimney	Stainless steel
Typology	N/A
Installation type	Wall freestanding
Motor location	Motor integrated in the hood
Operating mode	Convertible
Connection Rating	112 W
Current	0.51 A
Voltage	220-240 V
Frequenc	50 Hz
Approval certificates	N/A
Length of electrical supply cord	100 cm
Plug type	GB
Height of the chimney (mm)	330/630
Height of product, without chimney	166 mm
Net weight	6,9 Kg
Gross weight	8,67 Kg
Width of the product	600 mm
Height of the product	166 mm
Depth of the product	450 mm
Width of the packed product	650 mm
Height of the packed product	245 mm
Depth of the packed product	500 mm
Air exhaust	Yes

Features :

Remote control	N/A
Short description of the product	KH60A-F2LB SS-CH6C4BXUK
Type of control	Mechanical
Type of manual control devices	Knobs
Number of motors	1
Total power of the motors	110 W
Number of speed settings	3
Boost position	No
Maximum output air extraction	450 m³/h

Maximum output recirculating air	305 m³/h
Illumination setting	ON/OFF
Number of lights	2
Type of lamps used	LED diode
Total power of the lamps	2 W
Max. noise level	65 dB(A) re 1 pW
Diameter of air outlet	150
No-return airflow flap	Yes
Grease filter material	Washable aluminium
Odour filter	No

Energy label information / Performance :

Air flow at intensive or boost setting	N/A
Maximum Air flow	450 m³/h
Minimum air flow	252 m³/h
Total annual energy consumption	38,2 kWh/year
Energy efficiency class	B
Fluid Dynamic Efficiency class	C
Grease filtering efficiency class	B
Lighting efficiency	A
Noise level with boost position	N/A
Sound power at max. speed	65 dB
Sound power at min. speed	56 dB
Maximum extraction rate by extraction operation	450 m³/h
Energy efficiency index (2010/30/EC)	66,2 %
Fluid Dynamic Efficiency (2010/30/EC)	18,3
Grease filtering efficiency (2010/30/EC)	89,3 %
Lighting efficiency (2010/30/EC)	59,0
Noise level with boost position	N/A
Power consumption in standby mode (2010/30/EC)	N/A
Power consumption in off-mode - NEW (2010/30/EC)	N/A