1/3

PRODUCT FICHE

Appliance status: R Valid from: 25. 02. 2022 00:00:00 Last modification: 3. 03. 2022 01:36:10

# Hisense

#### **Built-In Oven** 741060 BI64211PB

#### USP:

Quadruple glazed oven door with one heat deflector (UltraCoolDoorQuadro)

If you have a toddler running around, these oven doors are completely cool to touch. Because of the advanced design with special glazing the heat stays in the oven, making it safe for you, your kids and pets.

Door hinge Classic door hinge Oven type Multisystem oven BigSpace - 77 I SuperSize baking area

Touch-free Inox Maximum oven temperature 300 °C

Cooling fan Dynamic oven cooling plus - DC+

Super Size

Even Bake

This advanced technology is why your cooking is always on point. Everything you put in this oven is cooked evenly thanks to slightly rounded large cavity which together with smartly positioned special heaters enables excellent and even hot air distribution. This means crispy on the outside, juicy on the inside. Big glass door and great inside illumination enable you to check on your food anytime without opening the door and letting out hot air. Efficient and even cooking guaranteed.

Circular heater

Gentle Bake

Fast Preheat With this Fast Preheat you can start your cooking earlier. The oven reaches a temperature of up to 200°C in less than 5

minutes, which is much faster than standard preheating. This is very convenient for recipes that require a preheated oven. A light and sound signal informs your when the

desired temperature is reached.

Large infra heater

Air Fry Air-frying takes the guilt out of guilty-

pleasure snacks in a snap. Say goodbye to deep-fried chicken wings with fries and their calories, and welcome healthier versions using less or no oil. Now you can prepare low-fat meals and more healthy food with air frying directly in your Hisense oven, without having to buy an additional kitchen

appliance.

Frozen Bake Mode This function is perfect for cooking your store -bought frozen foods and other pre-prepared meals such as croissants, lasagne, French fries, chicken nuggets and other pre-baked frozen meat cuts and vegetables. Your

dinner will be ready quickly, without preheating.

Interior light Above Pizza Mode

Now you can enjoy your homemade pizza whenever. Maximum temperature of 300 degree and excellent heat distribution allow that pizza is baked in a very short time tasting just as delicious it would in any Italian

restaurant.

Gratin If you want your food all beautiful and crispy, we have a solution for you. Activate gratin function so the grill heater from above will deliver extremely high heat close to the surface of your food. Perfect crust is now just

a touch away.

Oven door switch Mechanical

Pro Grill

Extra Durable Enamel

741060 2/3

Pyrolytic Self-Clean

Remove stubborn oven grease with minimal effort by simply activating Pyrolytic Self-clean function. Ovens heats up to 500°C, burning down grease and grime, leaving behind only some residual ashes which you can wipe off with just a damp cloth once the oven is completely cooled down. During the process the oven is automatically locked down, making the cleaning completely safe.



### Basic information:

Brand         HISENSE           Commercial code         BI64211PB           Internal article number         741060           EAN code         3383782640452           Main colour of product         VZ065; Brushed stainless steel           Construction type         Built-In           Type of control         Mechanical           Microwave function         No           Are any hobs controls integrated?         Yes           Dorn Material         Glass           Energy input         Electricity           Cooking method         Multisystem           Electrical connection rating         3500 W           Current         0,0 A           Voltage         220-240 V           Frequency         50-80 Hz           Marks of conformity         CE           Length of electrical supply cord         150 cm           Plug type         Without plug, supply cord 3 x 1.5           Height of the product         595 mm           Width of the product         564 mm           Height of the product         600 mm           Width of the packed product         620 mm           Depth of the packed product         620 mm           Width of installation niche         600 mm
Internal article number         741060           EAN code         3838782640452           Main colour of product         V2065; Brushed stainless steel           Construction type         Bullt-In           Type of control         Mechanical           Microwave function         No           Are any hobs controls integrated?         Yes           Door Material         Glass           Energy input         Electricity           Cooking method         Multisystem           Electrical connection rating         3500 W           Current         0,0 A           Voltage         220-240 V           Frequency         50-60 Hz           Marks of conformity         CE           Length of electrical supply cord         150 cm           Plug type         Without plug, supply cord 3 x 1.5           Height of the product         595 mm           Width of the product         595 mm           Width of the packed product         660 mm           Width of the packed product         620 mm           Depth of installation niche         600 mm           Min width of installation niche         590 mm           Min height of installation niche         500 mm           Min height of installa
EAN code         3838782640452           Main colour of product         VZ065; Brushed stainless steel           Construction type         Built-in           Type of control         Mechanical           Microwave function         No           Are any hobs controls integrated?         Yes           Door Material         Glass           Energy input         Electricity           Cooking method         Multisystem           Electrical connection rating         3500 W           Current         0,0 A           Voltage         220-240 V           Frequency         50-60 Hz           Marks of conformity         CE           Length of electrical supply cord         150 cm           Plug type         Without plug, supply cord 3 x 1.5           Height of the product         595 mm           Width of the product         595 mm           Up of the product         660 mm           Width of the packed product         620 mm           Up of the packed product         620 mm           Depth of installation niche         600 mm           Min height of installation niche         600 mm           Min height of installation niche         600 mm
Main colour of product         VZ065; Brushed stainless steel           Construction type         Bullt-In           Type of control         Mechanical           Microwave function         No           Are any hobs controls integrated?         Yes           Door Material         Glass           Energy input         Electricity           Cooking method         Multisystem           Electrical connection rating         3500 W           Current         0,0 A           Voltage         220-240 V           Frequency         50-60 Hz           Marks of conformity         CE           Length of electrical supply cord         150 cm           Plug type         Without plug, supply cord 3 x 1.5           Height of the product         595 mm           Width of the product         595 mm           Leight of the packed product         660 mm           Width of the packed product         675 mm           Min height of installation niche         600 mm           Max height of installation niche         500 mm           Min width of installation niche         560 mm
Construction type         Built-in           Type of control         Mechanical           Microwave function         No           Are any hobs controls integrated?         Yes           Door Material         Glass           Energy input         Electricity           Cooking method         Multisystem           Electrical connection rating         3500 W           Current         0,0 A           Voltage         220-240 V           Frequency         50-60 Hz           Marks of conformity         CE           Length of electrical supply cord         150 cm           Plug type         Without plug, supply cord 3 x 1.5           Height of the product         595 mm           Width of the product         595 mm           Up of the product         660 mm           Width of the packed product         620 mm           Width of the packed product         620 mm           Min height of installation niche         590 mm           Max height of installation niche         600 mm           Min width of installation niche         600 mm
Type of control Microwave function No Are any hobs controls integrated? Door Material Energy input Cooking method Electrical connection rating Current Current Current Voltage Frequency Frequency Marks of conformity Length of electrical supply cord Buy bye Height of the product Height of the product Height of the product Height of the packed product Height of installation niche Min width of installation niche Min width of installation niche Min width of installation niche Micros Glass Glass Electricity Glass Buyes Electricity Multisystem Electricity Class Bullisystem Soo W Cutrent Current Current Current Current Current Cooking method Multisystem Solo W Class Blectricity Class
Microwave function No Are any hobs controls integrated? Yes Door Material Glass Energy input Electricity Cooking method Multisystem Electrical connection rating 3500 W Current 0,0 A Voltage 220-240 V Frequency 50-60 Hz Marks of conformity CE Length of electrical supply cord 150 cm Plug type Without plug, supply cord 3 x 1.5 Height of the product 595 mm Width of the product 595 mm Depth of the product 560 mm Width of the packed product 660 mm Width of the packed product 620 mm Depth of installation niche 600 mm Min height of installation niche 600 mm Min width of installation niche 560 mm
Are any hobs controls integrated?  Door Material Energy input Cooking method Electricity Cooking method Electrical connection rating 3500 W Current 0,0 A Voltage Current Voltage Frequency Frequency Frequency Electrical supply cord 150 cm Plug type Height of the product Width of the product Height of the packed product Height of the packed product Height of the packed product Min height of installation niche Min width of installation niche  Min width of installation niche  Geleas  Glass Electricity  Multisystem  Blectrical y  Multisystem  S300 W  Autisystem  S400 W  Multisystem  S400 W  S400 W  S400 W  Multisystem  S400 W  S400 W  S400 W  S400 W  S400 W  Multisystem  S400 W  S
Door MaterialGlassEnergy inputElectricityCooking methodMultisystemElectrical connection rating3500 WCurrent0,0 AVoltage220-240 VFrequency50-60 HzMarks of conformityCELength of electrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWidth of the product595 mmDepth of the product564 mmHeight of the packed product660 mmWidth of the packed product620 mmDepth of installation niche590 mmMax height of installation niche600 mmMin width of installation niche560 mm
Energy inputElectricityCooking methodMultisystemElectrical connection rating3500 WCurrent0,0 AVoltage220-240 VFrequency50-60 HzMarks of conformityCELength of electrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWidth of the product595 mmDepth of the product564 mmHeight of the packed product660 mmWidth of the packed product675 mmMin height of installation niche590 mmMax height of installation niche600 mmMin width of installation niche600 mmMin width of installation niche600 mm
Cooking methodMultisystemElectrical connection rating3500 WCurrent0,0 AVoltage220-240 VFrequency50-60 HzMarks of conformityCELength of electrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWidth of the product595 mmDepth of the product564 mmHeight of the packed product660 mmWidth of the packed product620 mmDepth of the packed product675 mmMin height of installation niche590 mmMax height of installation niche600 mmMin width of installation niche560 mm
Electrical connection rating Current O,0 A  Voltage 220-240 V  Frequency 50-60 Hz  Marks of conformity CE Length of electrical supply cord Plug type Without plug, supply cord 3 x 1.5  Height of the product Width of the product Depth of the product Width of the packed product Width of the packed product Width of the packed product Field to the packed product Width of the packed product Width of the packed product Field to fine packed product Field to fiel
Current 0,0 A  Voltage 220-240 V  Frequency 50-60 Hz  Marks of conformity CE  Length of electrical supply cord 150 cm  Plug type Without plug, supply cord 3 x 1.5  Height of the product 595 mm  Width of the product 595 mm  Depth of the product 564 mm  Height of the packed product 660 mm  Width of the packed product 620 mm  Depth of the packed product 675 mm  Min height of installation niche 590 mm  Max height of installation niche 600 mm  Min width of installation niche 560 mm
Voltage220-240 VFrequency50-60 HzMarks of conformityCELength of electrical supply cord150 cmPlug typeWithout plug, supply cord 3 x 1.5Height of the product595 mmWidth of the product595 mmDepth of the product564 mmHeight of the packed product660 mmWidth of the packed product620 mmDepth of the packed product675 mmMin height of installation niche590 mmMax height of installation niche600 mmMin width of installation niche600 mmMin width of installation niche560 mm
Frequency Marks of conformity CE Length of electrical supply cord Plug type Without plug, supply cord 3 x 1.5 Height of the product S95 mm Width of the product S964 mm Height of the packed product Height of the packed product Width of the packed product For the packed produc
Marks of conformity Length of electrical supply cord Plug type Without plug, supply cord 3 x 1.5 Height of the product 595 mm Width of the product 595 mm  Depth of the product 566 mm  Height of the packed product 660 mm Width of the packed product 675 mm  Min height of installation niche Min width of installation niche 560 mm
Length of electrical supply cord  Plug type Without plug, supply cord 3 x 1.5  Height of the product 595 mm  Width of the product 595 mm  Depth of the product 564 mm  Height of the packed product 660 mm  Width of the packed product 620 mm  Depth of the packed product 675 mm  Min height of installation niche Max height of installation niche Min width of installation niche Min width of installation niche 560 mm
Plug type Without plug, supply cord 3 x 1.5  Height of the product 595 mm  Width of the product 595 mm  Depth of the product 564 mm  Height of the packed product 660 mm  Width of the packed product 620 mm  Depth of the packed product 675 mm  Min height of installation niche 590 mm  Max height of installation niche 600 mm  Min width of installation niche 560 mm
Height of the product 595 mm Width of the product 595 mm Depth of the product 564 mm Height of the packed product 660 mm Width of the packed product 620 mm Depth of the packed product 675 mm Min height of installation niche 590 mm Max height of installation niche 600 mm Min width of installation niche 560 mm
Width of the product 595 mm  Depth of the product 564 mm  Height of the packed product 660 mm  Width of the packed product 620 mm  Depth of the packed product 675 mm  Min height of installation niche 590 mm  Max height of installation niche 600 mm  Min width of installation niche 560 mm
Depth of the product 564 mm  Height of the packed product 660 mm  Width of the packed product 620 mm  Depth of the packed product 675 mm  Min height of installation niche 590 mm  Max height of installation niche 600 mm  Min width of installation niche 560 mm
Height of the packed product Width of the packed product Depth of the packed product Final Pa
Width of the packed product Depth of the packed product Min height of installation niche Max height of installation niche Min width of installation niche  Min width of installation niche  500 mm  600 mm  600 mm
Depth of the packed product  Min height of installation niche  Max height of installation niche  Min width of installation niche  600 mm  Min width of installation niche  560 mm
Min height of installation niche  Max height of installation niche  Min width of installation niche  590 mm  600 mm  560 mm
Max height of installation niche  Min width of installation niche  560 mm
Min width of installation niche 560 mm
***************************************
14
Max width of installation niche 564 mm
Depth of installation niche 550 mm
Net weight 31,1 Kg
Gross weight 33,1 Kg
Automatic programmes No
Type of control setting and signalling devices BIO21 ICON LED PYRO sensor control
Color / Material front VZ065; Brushed stainless steel
Grill power 0 W

## Features:

Temperature control

Short description of the product	BO3PY6C02-5 - BI64211PB - RL_ESSL
Timer	Yes
Integrated Cleaning system	Easy to clean enamel
Grids	1
Time control	No control of the time
Time-setting Options	No delay option
Trays	1
Control panel information	N/A
Oven interior	Enamelled steel
Motorized Turn Spit	N/A
Additional equipment included	Deep baking pan - 1 Oven grid - 1
Safety device	Oven door switch
Oven lighting	Yes
Position of interior lights	N/A
Meat probe	No
Oven guides	Wire type 1x

N/A

## Energy label information / Performance :

The power consumption in off-mode	1,0 W
Energy consumption per cycle conventional (2010/30/ES)	0,97 kWh/Zyklus
Energy consumption gas oven per cycle conventional (2010/30/ES)	0,0 Mj
Energy consumption per cycle forced air convection (2010/30/ES)	0,71 kWh/cycle
Usable volume of cavity (2010/30/ES)	77

Number of cavities - NEW (2010/30/EC)	1
Energy consumption gas oven per cycle conventional - NEW (2010/30/EC)	0,00
Energy efficiency index (2010/30/EC)	81,6
Energy efficiency class	A+
Energy consumption conventional	0,97 kWh
Noise	42 db(A)re 1 pW
Energy consumption forced air convection	0,71 kWh
Useable volume (of cavity)	77
Product size	Large