Supplier name or trademark

Haier

Model identifier	HW80-B14939S8
Capacity cotton (kg)	8
Energy efficiency class, on a scale of A (more efficient) to G	Α
Annual energy Consumption [kWh/annum] (1)	0
ENERGY CONSUMPTION 60° FULL LOAD (kW) (2)	0
ENERGY CONSUMPTION 60° PARTIAL LOAD (kW) (2)	0
ENERGY CONSUMPTION 40° PARTIAL LOAD (kW) (2)	0
Power Consumption of the off-mode [W]	
Water consumption annual (I/annum) (3)	0
Spin drying performance class from G (min) to A (max)	HW80-B14939S8
Maximum spin speed (rpm) (4)	1400
Moisture content % on dry load after max. spin (5)	0
Average washing time cotton 60C (full load) (min)	0
Average washing time cotton 60C (partial load) (min)	0
Average washing time cotton 40C (partial load) (min)	0
Duration of the left-on mode (min)	0
Airborne acoustical noise emissions (Washing phase) [dB]	53
Airborne acoustical noise emissions (Spinning phase) [dB]	67
Built-in / Free standing	Freestanding

<sup>1)</sup> Based on 220 standard washing cycles for cotton programmes at 60°C and 40°C at full and partial load, and the consumption of the low- power modes. Actual energy consumption will depend on how the appliance is used.\n2) The "standard 60°C cotton" at full and partial load and the "standard 40°C cotton" at partial load are the standard washing programmes to which the information in the label and the fiche relates. Standard 60°C cotton and standard 40°C cotton are suitable to clean normally soiled cotton laundry and are the most efficient programmes in terms of combined energy and water consumption. Partial load is half the rated load.\n3) Based on 220 standard washing cycles for cotton programmes at 60°C and 40°C at full and partial load. Actual water consumption will depend on how the appliance is used.\n4) For the standard 60 °C at full

Product fiche pursuant to Delegated Regulation (EU) no. 1061/2010

and partial load or the 40°C at partial whichever is lower.\n5) Attained for 60 °C cotton at full and partial load or the 40°C at partial whichever is higher.\n6) Based on washing and spinning phases for the standard 60°C cotton programme at full load.